

**UCV**

Chip Type, Low Impedance.

- Chip type, low impedance temperature range up to +105°C.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU, (EU)2015/863).
- AEC-Q200 Qualified. Please contact us for details.



For SMD



Low Impedance


**UCM**  
 Smaller  
 Higher capacitance
**UCV****■ Specifications**

Item	Performance Characteristics						
Category Temperature Range	-55 to +105°C						
Rated Voltage Range	16 to 35V						
Rated Capacitance Range	220 to 1500μF						
Capacitance Tolerance	±20% at 120Hz, 20°C						
Leakage Current ≈	After 2 minutes' application of rated voltage at 20°C, leakage current is not more than 0.01CV (μA).						
Tangent of loss angle (tan δ)	Rated voltage (V)	16	25	35			
	tan δ (max.)	0.16	0.14	0.12			
Stability at Low Temperature	Rated voltage (V)	16	25	35			
	Z(-25°C) / Z(+20°C)	2	2	2			
	Z(-40°C) / Z(+20°C)	3	3	3			
	ZT / Z20 (max.)	4	3	3			
Z(-55°C) / Z(+20°C)							
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 105°C.						
	Capacitance change	Within ±30% of the initial capacitance value					
	tan δ	200% or less than the initial specified value					
	Leakage current	Less than or equal to the initial specified value					
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.						
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.						
Marking	Black print on the case top.						



\* I : Leakage Current (μA), C : Rated Capacitance (μF), V : Rated Voltage (V)

**■ Chip Type**

(φ 6.3)



(φ 8,10)

**Type numbering system (Example : 35V 220μF)****Voltage**

V	16	25	35
Code	C	E	V

**Standard (mm)**

DC	6.3×7.7	8×10	10×10
A	2.4	2.9	3.2
B	6.6	8.3	10.3
C	6.6	8.3	10.3
E	2.2	3.1	4.5
L	7.7	10	10
H	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1

**● Frequency coefficient of rated ripple current**

Frequency	50Hz	120Hz	300Hz	1kHz	10kHz or more
Coefficient	0.35	0.50	0.64	0.83	1.00

● Dimension table in next page.

CAT.8100M

**UCV**

## ■ Dimensions

Rated Voltage (V) (code)	Rated Capacitance ( $\mu$ F)	Case Size $\phi$ D×L(mm)	$\tan \delta$	Leakage Current ( $\mu$ A) (at 20°C after 2 minutes)	Impedance ( $\Omega$ ) max. (20°C/100kHz)	Rated Ripple (mArms) (105°C/100kHz)	Part Number
16 (1C)	470	6.3×7.7	0.16	75.2	0.16	600	UCV1C471MCL1GS
	820	8×10	0.16	131.2	0.08	850	UCV1C821MNL1GS
	1500	10×10	0.16	240	0.06	1190	UCV1C152MNL1GS
25 (1E)	330	6.3×7.7	0.14	82.5	0.16	600	UCV1E331MCL1GS
	560	8×10	0.14	140	0.08	850	UCV1E561MNL1GS
	1000	10×10	0.14	250	0.06	1190	UCV1E102MNL1GS
35 (1V)	220	6.3×7.7	0.12	77	0.16	600	UCV1V221MCL1GS
	470	8×10	0.12	164.5	0.08	850	UCV1V471MNL1GS
	680	10×10	0.12	238	0.06	1190	UCV1V681MNL1GS

- For taping specifications, recommended land size/soldering by reflow and minimum order quantity, please refer to the Guidelines for Aluminum Electrolytic Capacitors.