

Type numbering system ※ 1

1	2	3	4	5	6	7	8	9	10	11	12	13	14
Type	Series name		Rated voltage		Rated capacitance			Capacitance tolerance	Configuration		Size code		
Conductive polymer type (CA32,04)	P		Rated voltage (V)	Code	Rated voltage (V)	Code	Capacitance (μF)	Code	Cap. tol. (%)	Code		Miniature Type	
FPCAP (CA32,04)	R		2.5	0E	125	2B	0.1	0R1	± 10	K		Taped, lead cut / formed Please refer to the Guidelines for Aluminum Electrolytic Capacitors.	
Hybrid type	G		4	0G	160	2C	0.47	R47	± 20	M			
Aluminum electrolytic capacitors Chip type Radial lead type (CE32,04)	U		5.5	0L	180	2Z	1	010	-10 to +30	Q		Large Can Type	
			6.3	0J	200	2D	2.2	2R2	-10 to +50	T			
			10	1A	220	2P	22	220	Special	A		Specification code	
			16	1C	250	2E	220	221					
			20	1D	315	2F	2200	222					
Aluminum electrolytic capacitors Can type (CE621,622,692,694,695,331)	L		25	1E	350	2V	22000	223					
			35	1V	400	2G							
			50	1H	420	W6							
			63	1J	450	2W							
			80	1K	500	2H							
			100	2A	550	2L							
			110	2Q	600	2X							

※ Standard capacitance tolerance is ±20%(M), please contact us for any other tolerance requirements.

※ 1 Please contact us about the FPCAP part number.
Product type and series names are listed on the top left of the individual specification pages.